

Single Panic Bolt AR880 SE =

Application

Suitable for single or double doors with plain meeting stiles. Suitable for single doors up to 2440mm height x 1220mm wide (extended top shoots available).

- SUITABLE FOR USE IN OPEN PUBLIC AREAS (in accordance with BS EN1125: 1997)

- Please note: For double NON rebated plain edge doors fit 2 x AR880

Standards and Certification

Quality & Performance: Successfully type tested to all the requirements of BS EN1125: 1997 + A1:2001

3 7 6 1 1 3 2 2 A

Fire Safety: Included in a successful fire test to BS EN1634 Part 1: 2000. For use on 30 min fire doors

CE Marked: Declaration of conformity available on request

Standard Features

- Automatic top trip
- Two-point locking
- Diecast control boxes
- Follower on main box for use with ARRONE® locking attachments
- Anti-thrust device preventing leverage of top and bottom shoots
- Oval steel rods
- Self handing
- Supplied with "W" clip for use with a rim cylinder on external side
- "Push Bar To Open" signage supplied

Finishes

- Silver
- Gold
- Black
- Polished Brass
- Polished Stainless Steel – Polished Chrome
- Satin Stainless Steel – Satin Chrome
- RAL colours to special order only

Guarantee

- Supported by a 2 Year Guarantee

ID NO PRODUCT REF DESCRIPTION FINISH

8510689 AR880-SE Single Panic Bolt Silver

8510640 AR880-GE Single Panic Bolt Gold

8510696 AR880-SSS Single Panic Bolt SSS

8510654 AR880-PB Single Panic Bolt PB

8510577 AR880-BL Single Panic Bolt Black

8510584 AR880-



Price

£54.00 (Product reference 1739-0)