

# Lumberjack 650 Standard Set - 14 Kg

## Product Description

LUMBERJACK 650 is high specification, trowel applied adhesive, specifically designed for fixing all types of wooden floors directly onto most substrates. Based on the latest hybrid Polymer technology Lumberjack 650 is totally water and solvent free. Lumberjack 650 has an extended open time (ca. 60mins) for large areas application and ease of adjustability.

## Benefits

100% active, solvent and water free – will not cause warpage or curl of wood blocks/planks.

Permanently flexible – compensates for subfloor movement. .

Will bond wood directly to all common subfloors, e.g. concrete, wood, metal, ceramic tiled, vinyl, marble, granite and most natural stone floors.

Suitable for use with underfloor heating (due to high flexibility)

Odourless and off white in colour

Excellent gap filling properties for uneven surfaces

Full bed elastic product gives excellent sound deadening/acoustic properties.

## Limitations

Always check with flooring manufacturer re: any specific instructions/requirements specifically relating to their flooring before fitting floors.

Do not use against bitumen or substrates that bleed oil or plasticizers

Do not use, store or allow to cure below +5oC.

## Surface Preparation

PRELIMINARY COMPATIBILITY TESTS ARE RECOMMENDED FOR EVERY SURFACE. Always check moisture level of subfloor (typically below 3% max before placing) with a carbide hygrometer.

The surfaces to be glued must be sound, clean, dry and free from dust, grease and other contaminants. Existing floors must be free from all polish/wax. Clean existing floor tiling with caustic soda; rinse thoroughly and allow to dry. Residues of old adhesive must be removed mechanically as they may affect adhesion.



## Price

single pail (Product reference 5295-42912)	£80.86
two pails (Product reference 5295-42913)	£161.09