

Treatex Colour Tones Spruce 0.5l 1l 2.5l-

Coverage

1L will cover approximately 20m² in one coat depending on the timber and method of application.

2.5L will cover approximately 50m² in one coat depending on the timber and method of application.

Please note!

Clear Hardwax Oil must always be used as the final coat when Natural Hardwax Oil or Colour Tones are applied*

Preparation

Sand the surface to smooth bare wood using 80-120 grit sandpaper. Ensure that any previous finish has been fully removed. Remove dust, dirt and any other contaminants which may lead to uneven absorption of Colour Tones. Make sure the surface to be treated is thoroughly dry. Stir tins and ensure product is at room temperature before use. Enough Colour Tone should be purchased to complete the whole project and when more than one container is required it is advisable to mix them together before use. Various species of timbers will take colours differently, we strongly advise a small trial application prior to starting a project.

Application

One coat of Colour Tone should be brushed or rolled on. To ensure an even colour, remove excess product from the surface with a lint free cloth. Allow to dry - maintaining warmth and ventilation will enable the surface to dry within 3-6 hours. If excess product is not removed from the surface, Colour Tones will not dry properly! Once dry, seal with two coats of Treatex Clear Hardwax Oil which is available in Matt, Satin or Gloss sheen levels. The top coats of Clear Hardwax Oil are applied to prevent the natural pigments in our Colour Tones from wearing.



Price

| | |
|---|--------|
| Treatex Colour Tones Spruce 0.5l 11050d= (Product reference 6732-11142) | £13.73 |
| Treatex Colour Tones Spruce 2.5l = (Product reference 6732-11143) | £56.82 |
| Treatex Colour Tones Spruce 1l 11070e = (Product reference 6732-11144) | £23.54 |