

Osmo Raw 3044

For wooden floors, furniture surfaces and work tops
Perfect for light coloured wood species

Product description:

Transparent-tinted, matt wood finish, which combines all the advantages of oils and waxes in one unique product. Osmo Polyx®-Oil Tints Raw are resistant to water and dirt, very durable and smoothen wood surfaces. The Polyx®-Oil Tints Raw protects the wood almost invisibly. The original look of the wood can be kept – no emphasizing of the natural colour of the wood (no wetlook-effect). In comparison to conventional finishes, the natural vegetable oils and waxes allow for a harmonic, smooth surface result. Easy application – no need for a primer or sanding between coats – saves time and money. It meets the wood's natural demands: It is microporous and does not crack, flake, peel or blister. Resistant against wine, beer, cola, coffee, tea, fruit juice, milk and water in accordance with DIN 68861-1A (German industrial norm). When dry, the finish is safe for humans, animals and plants and is suitable for children's toys as per EN 71.3 (European norm) and fast to perspiration and saliva in accordance with DIN 53160 (German industrial norm).

Recommended use:

Ideal for all interior wooden floors as well as furniture and wooden kitchen worktop surfaces.

Colour tone:

3044 Raw transparent

Can sizes:

0.75 l, 2.5 l

Coverage:

1 l = approx. 30 m²

Do you have greyed or split wood, an old unknown brand finish or an old Osmo finish on the surface, smooth or sanded wood, grooved, planed or rough sawn wood and would like to know how much finish is required to treat the wood? You can find more information on the individual usage calculation under www.osmo.com coverage calculator.

Ingredients:

Based on natural vegetable oils and waxes (sunflower-oil, soyabean-oil, thistle-oil, carnauba-wax, candelilla-wax), paraffins, titanium dioxide (white pigment), siccatives (drying agents) and waterrepellent additives. Disaromatised white spirit (benzene-free). This product fulfils EU-Regulation (2004/42/EC) according to the VOC limit value of max. 500 g/l (Cat. A/i (2010)).

Detailed declaration of ingredients available upon request.

Technical data:

Specific gravity: 0.90-0.95 g/cm³

Viscosity: 25-38 s according to DIN 53211/4mm

Odour: low/mild, odourless after drying

Flashpoint: 88.05 °C according to DIN 53213

Storage:

Shelf life is 5 years or more if can is tightly closed. Store in a dry place. If thickened by



Price

Osmo 3044 Raw 2.5L (Product reference 3419-5477)	£67.08
Osmo 3044 Raw 750ml (Product reference 3419-5478)	£26.63