

Treatex Ultra Hardwax Oil - Clear Soft satin

Easy to apply.
Quick drying.
No sanding required between coats.
Low odour.
Water resistant.
Withstands high temperatures.
Very durable.
Easy to clean with Treatex® Floor Care.
Easy to maintain with Treatex® Wax Polish.
Spot repairable.
Recommended for those with dust allergies; dirt and dust can be removed easily.
Meets with 2010 VOC emissions regulations.
Certified safe for use on children's toys: DIN EN 71-3.
Complies with regulation DIN 68861-1B: Resistance to substances such as wine, beer, coffee, tea, fizzy drinks etc.
Slip resistance certified for commercial use: DIN-51131, EN-13893.
Antibacterial, kills 99.99% of Staphylococcus aureus (MRSA), Escherichia coli (E.Coli) and Klebsiella pneumonia. Antibacterial properties tested using standard JIS Z 2801:2000.

One coat of Treatex® Traditional Colours should be brushed on to unfinished timbers and any excess should be clothed off. Finish with two coats of Treatex® Hardwax Oil Traditional Clear.

Hardener

Treatex® hardener is a chemical additive that can be used in commercial locations to increase surface hardness by at least 10% by mixing 10% hardener to Treatex® Hardwax oil. Can be used in both coats or just top coat if required.

Oily / Dense Timbers

Use Treatex® Isoparaffin when treating oily/dense timbers e.g. Iroko, Ipe, Teak, Jarrah, Merbau etc. Treatex® Isoparaffin is used to thin Treatex® Hardwax Oil Traditional so that it can properly penetrate into oily and dense timbers. For the first coat mix approximately 10% Treatex® Isoparaffin with Treatex® Hardwax Oil Traditional.



Price

Treatex Hardwax Oil CLEAR SATIN 0.5L + (Product reference 6742-11183)	£14.28
Treatex Hardwax Oil CLEAR SATIN 1L + (Product reference 6742-11184)	£23.82
Treatex Hardwax Oil CLEAR SATIN 2.5L + (Product reference 6742-11185)	£55.82
Treatex Hardwax Oil CLEAR SATIN 10L + (Product reference 6742-11186)	£209.53